

BEDELCO

TYRES



BEDELCO is active in the tyre business since more than 15 years and has developed its own brand LEVEL™ TYRE in 2006. Our technical knowledge and logistical capacities allow us to deliver tyres all over the world, providing the right for the job for professionals and/or endusers.

TYRE RANGE : - **OTR tyres** : from '24 to "63, for loaders, dumpers, graders, cranes,...

Main brand proposed : Hilo, Belshina, Leveltyre,...

- **Truck tyres** : Annaite, Double Star, Belshina,...

- **Agricultural tyres** : Belshina, Dneproshina,...

- **Retread truck tyres** (in Romania only)

LOCATION : Headquarter : BEDELCO SPRL, Belgium

Subsidiaries : BEDELCO AL DJAZAÏR, Algeria – BEDELCO EAST EUROPE, Romania

Offices : purchasing office in China, Representative Office in Belarus

BEDELCO sprl
TYRES

BEDELCO EAST EUROPE
Pneu Maxx
IMPORTATOR SI DISTRIBUTOR ANVELOPE

BEDELCO
TYRES
REPRESENTATION OFFICE

BEDELCO
Al Djazair sarl
PNEUS

BEDELCO
TYRES
PURCHASING OFFICE





B-103
7.50-20



B-19A
5.00-10



Bel PT-5
10.00-16



Bel PT-5M
9.00-16
10.00-16



Bel-104
13.0/75-16



Bel-111
520/70R38
520/70R38LS



Bel-126
580/70R42



Bel-129
480/70R30



Bel-131
480/70R38



Bel-134
480/70R34



Bel-136
480/65R24



Bel-139
16X6.50-8



Bel-144
540/65R30



Bel-15
20.8R38



Bel-163
14.9R30



Bel-17
13.6-20



Bel-27
18.4R30



Bel-31
9.00R20



Bel-68
14.9R24



Bel-79
16.5-18



Bel-83M
28LR26



Bel-87
20.0/60-22.5



Bel-89
360/70R24



Bel-90
420/70R24



Bel-91
24.0/50-22.5
24.0/50-22.5LS



Bel-92
10.0/75-15.3



Bel-93
620/75R26



BF-223
9.00-20



D-2A
15.5R38



D-62
15.5R38



D-66
6.50-16



D-71
540/70R24



DC-10
480/70R24



DE-11
18.4R38



DE-13
18.4R34



DE-15
11.2R44



DE-16
9.5R44



DE-17
9.5R48



DE-2
9.00-20



DE-3
11.2R20



DE-5
480/70R38



DE-6
16.9R38



DE-8
14.9R24



DF-16A
28.1-25



DP-17
10.00-16



DT-111
6.50-16



DT-129
14.00-38



DT-139
28.1R26



DT-141
750/70R26



DT-144
6.00-16

Size	Brand	Type	Star/Ply rating	Pattern	Load/Speed Index	Standard Rim	Section Width (mm)	Overall Diam (mm)	Max Load (Kgs)	Standard Pressure (Kpa)	Max speed (km/h)	Tread Depth (mm)	Remarks
10.0/75-15.3	BELSHINA	Diagonal	8/10	Bel-92	119/123 A6	9.00-15.3	266	760	1360/1550	310/390	30	10	TT
10.00-16	BELSHINA	Diagonal	10	Bel PT-5M	125 A8	6.00F/6.50F	270/275	894	1650	320	30	12	TT
	BELSHINA	Diagonal	10	Bel PT-5	125 A6	6.00F/6.50F	259/264	894	1650	280	40		TT
	DNEPROSHINA	Diagonal	10	DP-17	125 A8	6.50F/6.00F	264	900	1650	325	40		TT
11.2-20	BELSHINA	Diagonal	8	F-35-1	114 A6	W10/W9/W7	284	985	1180	210	30	35	TT
11.2R20	DNEPROSHINA	Radial		DE-3	111 A8	W10/W7/W9	284	995	1090/1400	160/240	40		TT
11.2R32	DNEPROSHINA	Radial		DT-3	117 A8	W10/W9/W8	284	1300	2120	360	40		TT
11.2R44	DNEPROSHINA	Radial		DE-15	133 A8	W10/W9	284	1605	2060	320	40		TT
	DNEPROSHINA	Radial		DE-15	140 A8	W10/W9	284	1605	2500	360	40		TT
12.4L-16	BELSHINA	Diagonal	8	Fbel-160	111 A6	W11/W10/W8	327/317/297	930	1085	220	30	25	TT
	BELSHINA	Diagonal	8	Fbel-160M	111 A6	W11/W10/W8	327/317/297	930	1085	220	30	25	TT
13.0/75-16	BELSHINA	Diagonal	8/10	Bel-104	130/135 A6	W11/W8	336	920	1900/2170	240/310	30	16	TT
	BELSHINA	Diagonal	8/10	Fbel-340	130/135 A6	W11/W8/W9	336/325/329	900	1900/2170	240/310	30	10	TT
13.0/75R16	DNEPROSHINA	Radial	8	DT-76	130 A8	W11/W8	336	900	1900	240	40		TT
13.6-20	BELSHINA	Diagonal	8	Bel-17	120 A8	W12	345	1060	1400	160	40	25	TT

Size	Brand	Type	Star/Ply rating	Pattern	Load/Speed Index	Standard Rim	Section Width (mm)	Overall Diam (mm)	Max Load (Kgs)	Standard Pressure (Kpa)	Max speed (km/h)	Tread Depth (mm)	Remarks
13.6R38	DNEPROSHINA	Radial	6	F-287	128 A8	W12/DW12/ W11/DW11	345	1550	1800	160	40		TT
14.00-38	DNEPROSHINA	Diagonal		DT-129	133 A6/137 A6		355	1580	2060	160	40		TT
14.9R24	BELSHINA	Radial		Bel-68	126 A8	W13	378	1245	1700	160	40	45	TT
	DNEPROSHINA	Radial		DE-8	126 A8	W13/W12	378	1245	1700	160	40		TT
14.9R30	BELSHINA	Radial		Bel-163	129 A8	W13/DW13/ W12/DW12	640	1400	1850	160	40		TL
15.5R38	BELSHINA	Radial	8	F-2A BEL	134 A8	W14L/DW14L	394	1570	2120	160	40	35	TT
	DNEPROSHINA	Radial	8/10	D-2A	134 A8	W14L	394	1570	2120	160	40		TT
	DNEPROSHINA	Radial	8	F-2A DNE	134 A8	W14L	394	1570	2120	160	40		TT
	DNEPROSHINA	Radial	8/10	D-62	134 A8	W14L	394	1570	2120	160	40		TT
16.0-20	BELSHINA	Diagonal	8/12/14	F-64GL-1	120 A8	DW13/DW14/ DW12/W12	405/395	1075	1750/3355/ 3670	170/300/ 350	30	30	TT
16.5/70-18	BELSHINA	Diagonal	10/14	KF-97 BEL	149/153 A6	330-462	425	1065	3250/3650	370/410	30	15	TT
	DNEPROSHINA	Diagonal	10	KF-97 DNE	149/153 A6	300-462	425	1065	3250	370	30		TT
16.5-18	BELSHINA	Diagonal	2	Bel-79	48 F	330-462	440	1085	180	50	80	9.5	TT
16.9R30	BELSHINA	Radial		F-39	137 A8	W15L/W14L/DW14	429/420	1462	2300	160	40	46	TT
	BELSHINA	Radial		F-245-1	137 A8	W15L/W14L/DW14	429/420	1470	2300	160	40	45	TT
	DNEPROSHINA	Radial	8	F-43	136 A6	W15L	429	1462	2240	170	30		TL

Size	Brand	Type	Star/Ply rating	Pattern	Load/Speed Index	Standard Rim	Section Width (mm)	Overall Diam (mm)	Max Load (Kgs)	Standard Pressure (Kpa)	Max speed (km/h)	Tread Depth (mm)	Remarks
16.9R38	BELSHINA	Radial	8	F-52	141 A8	W15L/W14L/DW14L	429	1675	2575	160	40	50	TT
	DNEPROSHINA	Radial		DE-6	141 A8	W15L/W14L/DW14L	429	1675	2575	160	40	TT	
16X6.50-8	BELSHINA	Diagonal	6	Bel-139	76 A5	5.375	165	427	400	400	25		TT
18.4-24	BELSHINA	Diagonal	8/10	F-148	135 A6	DW16	467	1400	3020/2890	160/220	25/30	40	TT
18.4R24	DNEPROSHINA	Radial		DT-30	139 A8	W16L/DW16/W15L/ DW15L	467	1395	2430	160	40		TT
18.4R26	DNEPROSHINA	Radial		DT-18	140/147 A8	W16L/DW16/W15L/ DW15L	467	1440	2500	160	40		TT/TL
18.4R30	BELSHINA	Radial		Bel-27	144 A8	DW14L/W15L/W16L	467	1545	2800	180	40	45	TT
18.4R34	BELSHINA	Radial		F-11	144 A8	W16L/W15L/DW16L	467	1645	2800	160	40	38	TT
	DNEPROSHINA	Radial		DE-13	144/151 A8	W16/DW16L/W15L	467	1645	2800	160	40		TT
	DNEPROSHINA	Radial		DE-13	157/160 A8	W16/DW16L/W15L	467	1645	2800	160	40		TL
18.4R38	BELSHINA	Radial		F-111	146 A8	W16L/DW16L/W15L	467	1750	3000	160	40	45	TT
	DNEPROSHINA	Radial		DE-11	146/153 A8	W16/DW16L/W15L	467	1750	3000	160	40		TT
	DNEPROSHINA	Radial		DE-11	157/162 A8	W16/DW16L/W15L	467	1750	3000	160	40		TL
20.0/60-22.5	BELSHINA	Diagonal	12	Bel-87	156 A6	16.00-22.5	503	1170	4000	240	30	35	TL/TT

Size	Brand	Type	Star/Ply rating	Pattern	Load/Speed Index	Standard Rim	Section Width (mm)	Overall Diam (mm)	Max Load (Kgs)	Standard Pressure (Kpa)	Max speed (km/h)	Tread Depth (mm)	Remarks
20.8R38	BELSHINA	Radial		Bel-15	153/161 A8	W18L/W16L	528	1835	3650/4625	160/240	40	48	TT
21.3-24	BELSHINA	Diagonal	10/12	IYaV-79	140 A6/154 A8	DW18	540	1400	2500/3860	160/220	30/40	30	TT
21.3R24	DNEPROSHINA	Radial	10	FD-14A	140 A8	DW18	540	1400	2500	160	30		TT
	DNEPROSHINA	Radial	12	FD-14A	150 B	DW18	540	1400	3350	240	50		TT
22.0/70-20	BELSHINA	Diagonal	10	F-118A	156 A6	18-20	560	1300	4000	200	30	16	TT
23.1-26	DNEPROSHINA	Diagonal	12	I-242AB	153 A6	DW20	605	1621	3650	170	30		TT
23.1R26	DNEPROSHINA	Radial	12	F-37	148/153 A8	DW20	587	1605	3650	160	40		TT
	DNEPROSHINA	Radial	10	F-37	166 A8	DW20	587	1605	3150	120	40		TT
24.0/50-22.5	BELSHINA	Diagonal	12	Bel-91	160 A6	20.00-22.5	612	1155	4500	200	30	35	TL/TT
24.0/50-22.5LS	BELSHINA	Diagonal	12	Bel-91	160 A6	20.00-22.5	612	1155	4500	200	30	35	TL/TT
28.1-25	DNEPROSHINA	Diagonal	18	DF-16A	176 A8	24.00	710	1730	7100	260	40		TT
	DNEPROSHINA	Diagonal	22	DF-16A	185 B	24.00	720	1730	9250	360	50		TT
28.1R26	BELSHINA	Radial		FD-12 BEL	158/170 A6	DW24	750	1730	4200/6000	170/240	30	42	TT
	DNEPROSHINA	Radial	12	FD-12D	172 A6	DW24	750	1735	4250	160	40		TT
	DNEPROSHINA	Radial	12	FD-12 DNE	157/165 A6	DW24	750	1735	4125	160	30		TT
	DNEPROSHINA	Radial		DT-139	157 A8	DW24	750	1735	4125	160	40		TT